

SPRING LOADED BAYONET FITTING

Model - TC05

Special Features:

- Spring Loaded Design.
- Bayonet fitting size is available as per customer's requirements.
- Available in Various standard Sheath diameters and Sheath materials.
- Straight or Angular Mounting.
- Standard followed in general IEC 584.2 / ANSI MC 96.1

Applications:

- · Plastic Industries
- Injection Moulding Machine
- · Textile Industries

Specifications

STANDARD VERSION

No. Of Element	: Simplex					
No. of Element	·					
Element Type	Type J (Fe-CuNi)					
Accuracy	: Class '2' Tolerance as per IEC - 584.2 / ANSI MC - 96.1					
Hot Junction Type	: Ungrounded Junction					
Sheath Diameter	: 4.5mm					
Sheath Material	: AISI 316 SS					
Immersion Length	: 30mm					
Lead Wire Type	: PTFE / PTFE / SS Braided					
Lead Wire Length	: 3000mm					
Process Connection	: Spring Loaded Bayonet connector , ID=12mm					
Process Connection Type	: Double Slotted					
Mounting	: Straight or Angular					

Dimensional Details :

STRAIGHT TYPE Lead Wire Length Lead Wire Length Lead Wire with Spring Spring Loaded Bayonet Fitting Spring Loaded Bayonet Fitting

Note: Drawings are not to scale. All Dimensions are in mm.

SELECTION OF MODEL

(1) MODEL CODE

(2) NO OF ELEMENT

SIMPLEX	S
DUPLEX (Above Sheath Dia. 3mm)	D

(3) ELEMENT

Type K (NiCr-Ni)	K
Type J (Fe-CuNi)	J

(4) HOT JUNCTION TYPE

Grounded	G
Ungrounded	U

(5) SHEATH DIAMETER

3.0mm	3.0
4.5mm	4.5
6.0mm	6.0
8.0mm	8.0

(6) IMMERSION LENGTH

PLEASE SPECIFY IN mm

(7) LEAD WIRE LENGTH

PLEASE SPECIFY IN mm

(8) LEAD WIRE TYPE

PTFE Insulated	1
PTFE / PTFE Insulated	2
PTFE / PTFE / SS Braided	3
FG / FG / SS Braided	4

(9) OPTIONS

Accuracy - Class "1" as per Standard			
Calibration Certificate			
SS Tag Plate			
Process connection type with Single Slotted			
90° Angular Type Mounting			
Spring Loaded Bayonet Connector , ID=14mm			

Example	1	2	3	4	5	6	7	8	9
SELECTION OF MODEL	TC05	S	J	U	4.5	30mm	3000mm	3	xx

NESSTECH INC.

INTERNATIONAL SALES DEPARTMENT

1-12-1 Akanehama, Narashino-shi, Chiba 275-0024, JAPAN

PHONE +81-47-453-1182 F A X +81-47-453-0727

■ NESSTECH INSTRUMENTS PVT. LTD (INDIA)

TC05

S

U

4.5

30mm

3000mm

3

XX

Survey No. 26/2, "G" Type, Global Industrial Park, Near Nahuli Railwaycrossing, Village Valvada, Vapi, Tal Umbergaon, Dist Valsad-396191, Gujrat

TEL: +91-260-299-6920

■ NESS TECHNOLOGY (M) SDN BHD (MALAYSIA)

No. 42A Jalan PUJ 3/8, Taman Puncak Jalil, Bandar Putra Permai, 43300 Seri Kembangan, Selangor

TEL: +603-8940-1134/8940-1059 FAX: +603-8999-4133